




Max Power (Watts)	Series	Attenuation (dB)	Freq (GHz)	Connector	L" x OD"
2	612-dB-1	0 - 32	Hz - 4.0	N M / F	2.20 x 0.82
2	612-dB-2	0 - 32	Hz - 4.0	BNC M / F	1.82 x 0.57
2	612-dB-3	0 - 32	Hz - 4.0	BNC M / F	1.82 x 0.57
2	612-dB-3RP	0 - 32	Hz - 4.0	RP-TNC M / F	1.82 x 0.59
2	605-dB-1F3	3, 6, 10, 20 & 30	Hz - 6.0	N M / F	1.76 x 0.82
2	605-dB-1	3, 6, 10, 20, 30 & 40	Hz - 6.0	N M / F	1.76 x 0.82
2	605-dB-1	50 & 60	Hz - 6.0	N M / F	2.04 x 0.82
2	605-dB-3	3, 6, 10, 20, 30 & 40	Hz - 6.0	TNC M / F	1.36 x 0.630
2	605-dB-3F18	3, 6, 10, 20 & 30	Hz - 18.0	TNC M / F	2.07 x 0.56
2	605-dB-1F18	3, 6, 10, 20, 30 & 40	Hz - 18.0	N M / F	1.76 x 0.82
2	662-dB-1	0 - 32	Hz - 4.0	SMA M / F	1.31 x 0.31
2	662-dB-1RA	0 - 32	Hz - 4.0	SMA M/F (Right Angle)	1.31 x 0.31
2	663-dB-1	0 - 32	Hz - 4.0	QMA M / F	1.63 x 0.41
2	665-dB-1F3	3, 6, 10, 20 & 30	Hz - 6.0	SMA M / F	0.86 x 0.28
2	665-dB-1F3	30 & 40	Hz - 6.0	SMA M / F	0.97 x 0.28
2	665-dB-1F3RP	3,6,10,20 & 30	Hz - 6.0	RP-SMA M / F	0.86 x 0.28
2	665-dB-1F3RP	30 & 40	Hz - 6.0	RP-SMA M / F	0.97 x 0.28
2	665-dB-1	0 - 12	Hz - 18.0	SMA M / F	0.86 x 0.28
2	665-dB-1	12 - 30 & 40	Hz - 18.0	SMA M / F	0.97 x 0.28
2	665-dB-1	50 & 60	Hz - 18.0	SMA M / F	1.49 x 0.28
2	665-dB-1H	3, 6, & 10	Hz - 18.0	SMA M / F	0.86 x 0.28
2	665-dB-1H	20 & 30	Hz - 18.0	SMA M / F	0.97 x 0.28
2	667-dB-1	3, 6 & 10	Hz - 26.5	2.92mm M / F	0.88 x 0.28
2	667-dB-1	20 & 30	Hz - 26.5	2.92mm M / F	1.01 x 0.28
2	668-dB-1H	3, 6, 10, 20 & 30	Hz - 40.0	2.92mm M / F	0.88 x 0.28
2.5	615-dB-1	30, 40, 50	Hz - 2.5	N M / F	3.20 x 1.00




605-dB-1F18



612-dB-1




612-dB-2



668-dB-1H



662-dB-1



662-dB-1RA



665-dB-1



615-dB-1

Input Power Attenuated

0 dB	1 dB	2 dB	3 dB	4 dB	5 dB	6 dB
0 %	20.57 %	36.9 %	49.88 %	60.19 %	68.38 %	74.88 %
7 dB	8 dB	9 dB	10 dB	20 dB	30 dB	40 dB
80.05 %	84.15 %	87.41 %	90 %	99 %	99.9 %	99.99 %